Product data sheet

Specifications



APC Home Office SurgeArrest 8 Outlets with 2 USB charging ports (5V, 2.4A in total), 120V

P8U2

| О | | | | |
|---|--|--|--|--|
| | | | | |
| | | | | |
| | | | | |

| Lead time | Usually in Stock |
|-----------|------------------|
| | |

| IVIAITI | |
|-----------------------|---------------|
| Main Input Voltage | 120 V |
| Input Connection Type | NEMA 5-15P |
| Cable length | 6 ft (1.83 m) |
| Number of cables | 1 |
| Provided equipment | User Manual |

Physical

| Color | Black |
|---------------------|-----------------------|
| Height | 1.26 in (3.2 cm) |
| Width | 3.50 in (8.9 cm) |
| Depth | 12.99 in (33 cm) |
| Net Weight | 1.72 lb(US) (0.78 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |

Input

| Input Frequency | 50/60 Hz |
|----------------------------|----------|
| Switching current capacity | 15 A |

Output

| Number of power socket outlets | 8 |
|--------------------------------|------------|
| Outlet standard | NEMA 5-15R |

Conformance

| UL 1449 TVSS Rating | L-N: 400 L-G: 500 N-G: 500 | |
|------------------------|----------------------------------|--|
| Product Certifications | MET Canada MET USA | |

Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Equipment protection policy Lifetime: \$100000

Environmental

| Ambient Air Temperature for Operation | 32113 °F (045 °C) |
|---------------------------------------|----------------------------|
| Relative Humidity | 095 % |
| Operating altitude | 010000 ft |
| Ambient Air Temperature for Storage | 5113 °F (-1545 °C) |
| Storage Relative Humidity | 095 % |
| Storage altitude | 050000 ft (0.0015240.00 m) |

Surge Protection and Filtering

| EP Joule Rating | 2525 J |
|---|--|
| NM Surge Response Time (ns) | 1 ns common mode |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 70 dB |
| Peak current | 20 kA common mode 40 kA per phase normal mode |
| Surge energy rating | 2630 J |

Ordering and shipping details

GTIN 731304323006

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.36 in (6 cm) |
| Package 1 Width | 13.98 in (35.5 cm) |
| Package 1 Length | 5.51 in (14 cm) |
| Package 1 Weight | 1.94 lb(US) (0.88 kg) |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 11.75 in (298.45 mm) |
| Package 2 Width | 14.75 in (374.65 mm) |
| Package 2 Length | 14.75 in (374.65 mm) |
| Package 2 Weight | 20.64 lb(US) (9.36 kg) |
| Number of Units in Package 3 | 288 |
| SCC14 | 10731304323003 |

Offer Sustainability

| Sustainable offer status Green Premium product | | |
|--|---|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov | |
| REACh Regulation | REACh Declaration | |
| REACh free of SVHC | Yes | |
| EU RoHS Directive | Compliant FURNHS Declaration | |

Life Is On by Schneider Electric Feb 26, 2023

| Mercury free | Yes | |
|----------------------------|-------------------------------|--|
| RoHS exemption information | Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | End of Life Information | |
| Contractual warranty | | |
| Warranty | Limited Lifetime | |

Recommended replacement(s)